

Degreaser 910

Degreaser

08/06/2023

L4.02.05 APAC
Old TDS No. L6.09.01

用途

スチール面や旧塗膜等の被塗物を脱脂洗浄する溶剤類



きれいなウエスを使用して表面を脱脂してください

使用できる被塗物

プライマーサフェーサーやラッカー系を含む旧塗膜に使用可能な汎用脱脂剤

使用方法

被塗物のグリース、油、ワックス、シリコン等の汚れなどを除去する為 2 枚の乾燥したきれいなウエスを使用し、1 枚に脱脂剤を染み込ませて被塗物表面を洗浄し、もう 1 枚のウエスは脱脂剤が乾燥する前に完全にふき取ります

注意: 脱脂の際には、きれいな新しいウエスを使用してください

使用後のウエスは、必ず脱脂剤を乾燥させてから廃棄処分してください

Degreaser 910

Degreaser

08/06/2023

L4.02.05 APAC

Old TDS No. L6.09.01

備考	トラックや商業車等の荷台部分を脱脂する際は、汚れ残留による密着不良を防ぐ為、下方向から上方向に脱脂してください。 脱脂剤は金属表面の温度を周囲の温度よりも若干低下させます。その際、表面に多少の湿気が発生することがあります 車を低温の所から温度の高い所へ移動した場合も同様です 密着不良を防ぐ為、被塗物温度が周囲の温度と同等になってから塗装を開始してください Degreaser 910 は、油、グリースなどの有機物質を除去しますが、塩分は除去しません
VOC 含有量 (理論上の数値)	Degreaser 910: 734g/L
製品の保管	製品の貯蔵安定期間は 20℃で保管された場合で表記しています 極端な温度変化を避けてください ※貯蔵安定期間については TDS S9.01.02 をご参照ください

アクゾノーベルコーティング株式会社 自動車補修塗料事業部
東京都国立市泉 4 丁目 8 - 7
Tel : 042 - 843 - 0081

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

AkzoNobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.sikkenscr.com