



## DULUX EASYCLEAN

MATT FINISH

WATER BASED

### PRODUCT INFORMATION

PRODUCT NAME	Dulux EasyClean
DESCRIPTION	Dulux EasyClean is a premium quality matt finish interior paint with KidProof+ technology that delays stains from penetrating further into the paint film and can be wiped away easily. With its Anti-bacterial property, it also aids to inhibit growth of certain bacteria on walls. Formulated with Dulux Colourguard Technology, it locks in colours to keep your wall looking beautiful for longer.
USAGE	Dulux EasyClean is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement and wallboards.
BENEFITS	<p>KidProof+ technology that delays stains from penetrating into the paint film and allows stains to be wiped away easily.</p> <p>Good stain resistance with common household stains.</p> <p>Anti-bacterial properties that aids to inhibit growth of certain bacteria* on walls.</p> <p>Colourguard Technology that keeps colours looking fresh longer.</p> <p>Low Odour &amp; Low VOC<sup>^</sup>.</p> <p>Singapore Green Label and SIRIM Eco-label certified<sup>^</sup>.</p> <p>No added lead &amp; mercury.</p> <p><sup>^</sup> Applicable to selected colours only.</p> <p><u>Note:</u></p> <p>* Under test conditions. Dulux EasyClean tested against the following 6 types of bacteria as per <i>JIS Z 2801:2010/A1:2012 Antibacterial products – Test for antibacterial activity and efficacy</i> to meet the anti-bacterial performance requirements:</p> <ul style="list-style-type: none"><li>- <i>Escherichia coli</i> (ATCC 8739)</li><li>- <i>Methicillin-resistant Staphylococcus aureus</i> MRSA (NCTC 12493)</li><li>- <i>Pseudomonas aeruginosa</i> (ATCC 15442)</li><li>- <i>Bacillus subtilis</i> (ATCC 6633)</li><li>- <i>Salmonella typhimurium</i> (ATCC 14028)</li><li>- <i>Staphylococcus aureus</i> (ATCC 6538P)</li></ul>
PACK SIZE	1, 5 and 18 litres
COLOUR RANGE	Refer to Dulux colour catalogue

### PERFORMANCE GUIDE

FILM PROPERTIES	Able to tolerate the levels of atmospheric humidity present in normal interior environments and can withstand any washing or cleaning of the wall with mild detergent only after the paint has cured for at least 7 days. Stain resistance is effective against common household stains.
THEORETICAL COVERAGE	Theoretical coverage which can be achieved under normal conditions is up to 11 – 12 m <sup>2</sup> /litre.

### PRODUCT DATA

COMPOSITION (nominal)	<p>Pigment : Lightfast non-lead pigments and mineral extenders</p> <p>Binder : Acrylic emulsion</p> <p>Solvent : Water</p>
VOLUME SOLIDS	White 39% (nominal), other colours will vary.



## DULUX EASYCLEAN

MATT FINISH

WATER BASED

### PRODUCT INFORMATION

#### APPLICATION

##### THINNING

Brush or Roller

For normal use, thinning is not usually necessary; but if required, add up to 1 part of clean water to 10 parts of paint (10%).

Conventional Spray

Add up to 1 part of clean water to 5 parts of paint (20%).

Airless Spray

Ready for use. Thinning is usually not required.

##### SPRAY RECOMMENDATIONS

Conventional Spray

Satisfactory through most equipment

Airless Spray

A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm<sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58 mm (23 thou) and a spray tip angle 65°

##### DRYING TIMES

Touch Dry

Single coat at standard thickness:

Recoat

Depends on temperature and humidity

2-3 hours

##### CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

#### PRE-APPLICATION

##### SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Dulux Sealer/Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 16%. These walls should be left to dry further.

##### SYSTEM INFORMATION

Powdery Surfaces

##### SEALER/PRIMER (1 COAT)

Dulux Weathershield Primer

Alkaline and/or New Surfaces

Dulux Exterior & Interior Wall Sealer

##### FINISH (MINIMUM 2 COATS)

Normal, Sound Surfaces

Dulux Exterior & Interior Wall Sealer

Dulux EasyClean

(Colour enhancer is advisable for vibrant colour)

#### PRECAUTION

##### HEALTH, SAFETY AND

##### ENVIRONMENT INFORMATION

Product Safety Data Sheet available upon request

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties

EC: 030325

Akzo Nobel Paints (Malaysia) Sdn Bhd  
(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338

Website: [www.dulux.com.my](http://www.dulux.com.my)

Email: [customercare.my@akzonobel.com](mailto:customercare.my@akzonobel.com)

**AkzoNobel**