ดูลักซ์ ซูเปอร์โคท ทู อิน วัน

สีน้ำมันผสมรองพื้นกันสนิมสำหรับ ไม้ และพื้นผิวอื่น ๆ



นวัตกรรมใหม่ล่าสุดของสีน้ำมันกันสนิม 2in1 สีน้ำมันเคลือบเงาเหล็กพร้อมรองพื้นกันสนิมในตัว ประหยัดเวลา ไม่ต้องทารองพื้น ผลิตจากพรีเมียมอะคริลิกเรซินให้ฟิล์มสีแข็งแกร่งทนทาน พร้อมคุณสมบัติทนทานการขีดข่วน ช่วยปกป้องกพื้นผิวได้ยาวนานกว่า มีคุณสมบัติเด่นในการป้องกันการเกิดสนิม และแห้งไว ช่วยให้ได้งานคุณภาพและประหยัดเวลาไปพร้อมกัน ทาได้ทั้งภายนอกและภายในอาคาร และทาได้หลากหลายพื้นผิว

- แห้งไวใน 1 ชั่วโมง จบงานได้เร็ว
- ทนทานต่อการกัดกร่อนจากสนิม
- ยึดเกาะโลหะผิวมันวาวทุกประเภท
- ฟิล์มสีทนทานต่อการขีดข่วนกว่าสีน้ำมันทั่วไป 3 เท่า
- ฟิล์มสีทนต่อแสง UV คงความเงาสดใสยาวนานไม่เหลืองตัว
- ไม่ผสมสารตะกั่วปรอท และสารโทลูอีน ซึ่งเป็นสารก่อมะเร็ง

ข้อมูลทางเทคนิคและคุณสมบัติของฟิล์มสี

ประเภทสี	สีน้ำมัน
ลักษณะฟิล์มสี	ด้านและเงา
ขนาดบรรจุ	1 ลิตร และ 3 ลิตร (สีสำเร็จรูปจากโรงงาน และสีสั่งผสมจากเครื่องผสมสี)
เฉดสี	โปรดดูจากแคตตาล็อคสีน้ำมันดูลักซ์ ซูเปอร์โคท ทูอินวัน
เนื้อสีโดยปริมาตร	30 - 40%
ระยะเวลาแห้งสัมผัส	อย่างน้อย 10 นาที
ระยะเวลาทาทับ	1 - 2 ชั่วโมง
ระยะเวลาแห้งสมบูรณ์	อย่างน้อย 7 วัน
การครอบคลุมพื้นที่ตามทฤษฎี	15 ตร.ม. / เที่ยว/ ลิตร

*พื้นที่ครอบคลุมเป็นค่าทางทฤษฎี อาจแตกต่างจากการใช้งานจริงไม่เกิน 20%

วิธีการใช้งาน

วิธีการใช้งาน	แปรง ลูกกลิ้ง หรือสเปรย์
การผสมก่อนใช้งาน	ใช้ได้ทันที หรือหากต้องการผสมด้วยทินเนอร์ ดูลักซ์ ซูเปอร์โคท T3000 (สำหรับสีน้ำมัน 2IN1) ตามอัตราส่วนของชนิดเครื่องมือที่ใช้งาน
การทำความสะอาด	ล้างทำความสะอาดอุปกรณ์ด้วยน้ำเปล่าทันทีหลังการใช้งาน
การเช็ดล้างฟิล์มสี	ควรทิ้งให้แห้งอย่างน้อย 14 วัน ก่อนล้างทำความสะอาดได้

ข้อแนะนำในการใช้สีสดเข้ม : ธรรมชาติของสีสด มีข้อจำกัดในเรื่องการกลบมิด อาจต้องเพิ่มจำนวนเที่ยวในการทา หรือใช้สีอ่อนกว่าในเฉดใกล้เคียงกันเป็นสีพื้น

ระบบการทาสี

ก่อนการทาสีทุกครั้ง พื้นผิวจะต้องแห้ง สะอาด ปราศจากฝุ่นละออง เศษซีเมนต์ คราบไขมัน และสิ่งสกปรกต่างๆ หากมีรอยแตกร้าวกว้างไม่เกิน 1 มม. ให้ซ่อมด้วยสีโป๊ว ดูลักซ์ อะคริลิค ฟิลเลอร์ 1040 ขัดแต่งให้เรียบ หากต้องการเพิ่มความเนียนเรียบให้กับพื้นผิว หรือปรับซ่อมผิวคอนกรีตที่มีปัญหา ให้ฉาบทั้งผนังด้วย ดูลักซ์ สมูทโอเวอร์ แล้วขัดแต่งให้เรียบและให้แน่ใจว่าผนังไม่มีรอยรั่วซึมของน้ำ เพื่อป้องกันฟิล์มสีโป่งพองภายหลัง

ขั้นที่ 1 การเตรียมพื้นผิว

- พื้นผิวเหล็กและโลหะเก่า	กรณีที่สีเดิมยังอยู่ในสภาพดี ควรขัดพื้นผิวให้มีความหยาบ กรณีสีเสื่อมสภาพ ให้ขูดสีเดิมและขูดสนิมออกให้หมด
- พื้นผิวเหล็กและโลหะใหม่	ควรทำความสะอาดพื้นผิวให้ปราศจากฝุ่น ผงสนิม และเช็ดคราบไขมันที่เคลือบสนิมออก เพื่อช่วยการยึดเกาะของเนื้อสี
- พื้นผิวไม้	เช็ดทำความสะอาดด้วยทินเนอร์ ดูลักซ์ ซูเปอร์โคท T3000 สำหรับสีน้ำมัน 2IN1 ขัดแต่งผิวให้เรียบ และทำความสะอาดพื้นผิวให้ปราศจากสีเดิมที่เสื่อมสภาพ ฝุ่นและคราบไข ทาสีน้ำมันดูลักซ์ ซูเปอร์โคท 2IN1 จำนวน 1-2 เที่ยว เพื่อป้องกันยางไม้
ขั้นที่ 2 การทาสีทับหน้า	คนเนื้อสีให้เข้ากันแล้วสามารถใช้ได้ทันที หรือผสมด้วยทินเนอร์ ดูลักซ์ ซูเปอร์โคท T3000 สำหรับสีน้ำมัน 2IN1 ตามอัตราส่วนของชนิดเครื่องมือที่ใช้งาน

หมายเหตุ : ทาทับหน้าอย่างน้อย 2 เที่ยว เพื่อประสิทธิภาพสูงสุด

มอก.2526-2567 สีเคลือบและรีดัก เฉพาะที่ทาภายนอกอาคาร

TGL-4-R4-14

CERTIFIED ISO 45001 UKAS MANAGEMENT SYSTEMS 001

การสงวนสิทธิ์เรียกร้อง: รายละเอียดข้างบนนี้มาจากการทดลอง เพื่อเป็นการแนะนำในการใช้งาน เนื่องจากสีถูกนำไปใช้ ในภาวะแตกต่างกัน บริษัทฯจึงไม่สามารถรับประกันในสิ่งอื่นใดนอกจากคุณภาพของสีเท่านั้น

บริษัท อั๊คโซ่ โนเบล เพ้นท์ส (ประเทศไทย) จำกัด (ชื่อเดิม บริษัท สี ไอ ซี ไอ (ประเทศไทย) จำกัด) 89 อาคาร คอสโม พาร์ค ชั้น 9 ยูนิต O,P ถนนป๊อปปูล่า บ้านใหม่ ปากเกร็ด นนทบุรี 11120
บริการลูกค้าสัมพันธ์ โทรศัพท์ (662) 572-8888 โทรสาร (662) 572-8889, www.dulux.co.th, www.facebook.com/duluxthailand

Dulux SuperCote 2IN1

Paint & Primer ENAMEL



The latest innovation in 2-in-1 anti-rust enamel paint A high-gloss enamel paint for metal surfaces with built-in anti-rust primer — saving time by eliminating the need for a separate primer application. Formulated with premium acrylic resin, it delivers a strong, durable film with excellent scratch resistance for long-lasting surface protection. It effectively prevents rust formation and dries quickly, ensuring both high-quality results and time efficiency. Suitable for both interior and exterior use, and compatible with a wide range of surfaces.

- **UV-resistant finish** maintains long-lasting gloss and brightness without yellowing.
- Adheres to all types of glossy metal surfaces.
- **Fast-drying in just 1 hour,** allowing for quicker project completion.
- Resistant to corrosion caused by rust
- Scratch-resistant coating – 3 times stronger than conventional enamel paint
- – carcinogenic substances

Technical Information & Paint Film Properties

Type of Paint	Acrylic emulsion
Finish	Semi-gloss and Matt
Pack size	1 and 5 U.S.Gallons (Ready-mixed) / 3 and 9 Litres (Tinting)
Colour Offer	Please refer Dulux Inspire colour card and Dulux Let's Colour fandeck
Volume Solids	30 - 40%
Touch Dry	At least 30 minutes
Recoat Dry	30 minutes - 2 hours
Full Cure	At least 7 days
Theoretical Coverage	35 - 40 Sq.m./coat/gallon

*Coverage is theoretical value and may differ from real application +-20%

Application

Application Method	Brush, Roller or Spray
Mixing Ratio	Ready to use. Can be thinned with 1 part of clean water to 10 parts of the product (10%)
Cleaning Up	Clean all equipments with clean water immediately after used
Washing Instructions of painted wall	Allow at least 14 days from application before cleaning.

Processes for strong colours : Vibrant/deep shades may require additional coats /or apply softer colour of the same shade as undercoat

Application System

Before painting every time, the surface must be cleaned until free from dirt and grease. If any, repair small cracks smaller than 1mm with Dulux Acrylic Filler 1040, then rub with sand paper. If requires extra smoothness to the wall, repair all imperfects by applying Dulux SmoothOver all over the wall. Rub down and make sure no cracks appeared for any possible water leakage in order to prevent paint film blistering later on.

Step 1: Surface Preparation

- *New masonry or previously painted in good condition*	Leave new masonry to be fully cured at least 1 month. Moisture not over 14%. Allow surfaces to dry out.
- *Previously painted or powdery surfaces*	Rub down and treat any area affected by fungus and algae with Dulux Weathershield Mouldwash and leave it overnight. Then rinse off with water and allow the wall to dry. Treatments such as sanding, burning off etc of paint films may generate hazardous dust and/or fumes. Wet sanding/flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.

Step 2: Priming

- *New masonry or previously painted in good condition*	Apply 1 coat of Dulux PrimerShield. Allow at least 30 minutes - 2 hours to dry before applying topcoat.
- *Previously painted, powdery surfaces, fiber-cement or skim coat surfaces*:	Apply 1 coat of Dulux Maseal and allow 10-12 hours drying prior applying topcoat.
- *New or previously painted with high moisture surfaces (max.25%)*	: Apply 1 coat of Dulux Weathershield Power Plus Primer and allow at least 2- 4 hours drying prior applying topcoat.
Step 3: Topcoat	Apply at least 2 coats of Dulux Inspire for Interior. Allow at least 30 minutes - 2 hours drying between coats.

TGL-4-R4-14

The information in this datasheet is given to the best of our knowledge based on laboratory testing and for use recommendation. As the product is often used under conditions beyond our control, the company cannot guarantee anything only the quality of the product.

AkzoNobel Paints (Thailand) Ltd. (Former ICI Paints (Thailand) Ltd.) 89 Cosmo Office Park, Floor 9, Unit O,P Popular Road, Banmai, Pakkred Nonthaburi 11120
Customer Service : Telephone (662) 572-8888 Fax (662) 572-8889, www.dulux.co.th, www.facebook.com/duluxthailand