DULUX EXTERIOR STUCCO

Product Name	Dulux Exterior Stucco
Description and Usage	Dulux Exterior Stucco is an exterior stucco that provides excellent surface filling and coverage. It will cover all surface imperfections on most exterior surfaces. Dulux Exterior Stucco contains anti-fungal, anti-bacterial additives & alkali resistance properties. Dulux Exterior Stucco is suitable on new or previously painted surfaces like concrete, plaster, brickwork, gypsum board, masonry, wood etc
Benefits	• Excellent filling & levelling properties • Excellent adhesion & elongation • Anti-fungal, anti-bacterial & alkali resistance properties • Hides minor surface imperfections and hairline cracks • Can also be used for filling up open grains of hard wood, MDF & other wooden surfaces
Pack Size	18 Litre
Colour Range	White

Film Properties

Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

Composition (nominal)	Binder : Acrylic copolymer Solvent : Water

Product Data

Finish	Thick paste / Matt
Volume Solids %	60 ± 2%
Typical WFT (microns) per coat	150 – 300 μm
Typical DFT (microns) per coat	90 – 180 μm
Theoretical Coverage	6.6 – 3.3 m^2/ litre / coat
Practical Spreading Rate	Depending on substrate, application method, application conditions and system, etc.
Specific Gravity	White 1.55 ± 0.05 kg/l

Drying / Over coating Information

° C	Touch Dry	Overcoating	Hard Dry
@ 30°c	1 - 2 hrs	3 - 5 hrs	24 hrs

Application	Scraper, Putty Knife or Trowel

Thinning Scrapper, Putty Knife, Trowel	Ready for use. Thinning is not required.

DULUX EXTERIOR STUCCO

Cleaning Up	Clean all equipment with water immediately after use.	
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.	
System Information *New, Normal, Sound Surfaces*	Surface preparation Dulux Acrylic Primer (1 coat) Dulux Exterior Stucco (1 or 2 coats)	Topcoat Dulux Exterior Topcoat range (2 coats or as advised)
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.	

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.