DULUX ACRYLIC PRIMER

Product Name	Dulux Acrylic Primer
Description and Usage	Dulux Acrylic Primer is an alkali resistant primer which has excellent penetration properties designed for interior & exterior applications. It also has anti-fungal properties for additional protection of the surface. Dulux Acrylic Primer is suitable on new or previously painted surfaces like concrete, plaster, brickwork, gypsum board, masonry, wood etc.
Benefits	• Good alkali resistance • Excellent penetrating properties • Anti-fungal properties • Suitable for Interior and Exterior applications
Pack Size	18 Litre
Colour Range	White

Film Properties

Water Resistance	Resistant to the levels of atmospheric humidity normally experienced in interior & exterior environment. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

Composition (nominal)	Binder : Acrylic copolymer Solvent : Water

Product Data

Finish	Smooth / Matt
Volume Solids %	34 ± 2%
Typical WFT (microns) per coat	85 – 100 μm
Typical DFT (microns) per coat	30 – 35 μm
Theoretical Coverage	11 – 10 m^2/ litre / coat
Practical Spreading Rate	Depending on substrate, application method, application conditions and system, etc.
Specific Gravity	White 1.36 ± 0.05 kg/l

Drying / Over coating Information

° C	Touch Dry	Overcoating	Full Dry
@ 30°c	25 - 35 min	1 - 2 hrs	4 - 6 hrs

Application	Brush, Roller, Spray

Thinning *Brush, Roller or Spray*	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 - 15 parts of paint (10% - 15%).

DULUX ACRYLIC PRIMER

Cleaning Up	Clean all equipment with water immediately after use.	
Surface Preparation	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi and algae with appropriate fungi and algae remover. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.	
System Information *New, Normal, Sound Surfaces*	Surface preparation Dulux Acrylic Primer (1 coat) Dulux Exterior Stucco (1 or 2 coats)	Topcoat Dulux Exterior Topcoat range (2 coats or as advised)
Health, Safety and Environment Information	Product Safety Data Sheet available upon request.	

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Decorative Paints L.L.C.
11th and 12th floor, Al Habtoor Business Tower
Dubai, UAE
Tel: (971)43990417
Email: dulux.arabia@akzonobel.com
Website: www.duluxarabia.com

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.