



Issued 10/2025

SATINWOOD

Dulux Satinwood is a solvent-based satin finish formulation that is tough, hardwearing and dirt resistant. Does not require an undercoat except where a strong colour change is required.

KEY BENEFITS

- Tough, Durable Finish
- Self Undercoating
- Dirt Resistant

PRODUCT INFORMATION

Typical Use

Suitable for use on interior wood and metal surfaces.

Pack Size

750ml 2.5L and 5L.

Colour Range

See appropriate Dulux Trade colour literature or visit dulux.ie

Film Properties

Chemical Resistance: Resistant to mild chemical fume attack but where there is heavy attack, such as actual contact with chemicals, specialist paint systems may be required (contact the Dulux Technical Advice Centre).

Heat Resistance: Generally resistant to heat up to 90°C, but some discolouration of light colours may occur at elevated temperatures.

Water Resistance: Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is very heavy and prolonged condensation.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 50 microns.

Dry: 25 microns.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Alkyd.

Solvent: White Spirit.

Volume Solids

PBW: 60% (nominal). Other colours will vary.

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease and wax.

New or bare surfaces should be primed with an appropriate Dulux primer.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Any surface defects should be filled with an appropriate Polycell Trade Polyfilla.

AkzoNobel



SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. The normal finishing process is 2 full coats of Dulux Satinwood. However, where a strong colour change is required, then a coat of an appropriate coloured Dulux

Undercoat may be necessary.

For best colour consistency, purchase sufficient tinted paint for entire job including touch-in at one time from the same source.

NOTE: Whilst leading-edge technology has been used in the development of this product, the nature of white solvent-based paints means that they will all discolour over time. The rate of discolouration is faster on areas with no or low natural or UV light. For long-lasting whiteness, we recommend the use of a water-based formulation such as Dulux Quick Dry Satinwood.

APPLICATION METHOD

Brush or roller only. For Health & Safety reasons relating to all solvent-based paints, spray application is not recommended. As with all solvent-based paints, do not apply at temperatures below 5°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre.

Issued 06/2014

SATINWOOD

Spray Recommendation This product should not be sprayed.

Drying Times

Single coat at standard thickness:

Touch Dry: 4-6 hours.

Recoat: 16-24 hours.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

- 1. Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. Use Paint Thinner::** Use a paint thinner to clean brushes and rollers.
- 3. Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
- 4. Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash water down the drain or onto the ground.

Storing & Responsible Disposal

Reuse, Recycle, or Donate: Whenever possible, reuse, recycle, or donate leftover paint. Find local services at mywaste.ie or consider advertising the paint locally. Many good causes often need paint, and a little can go a long way in brightening up community spaces!

2.Dispose Responsibly: Never pour paint or wastewater down drains or sinks. Dispose of them responsibly. Follow the instructions at mywaste.ie to recycle empty packs

3.Reuse Roller Cages: Roller cages can be reused. Simply remove the sleeve and store the cage in a dry, dust-free place.

4.**Dispose of Unusable Brushes and Sleeves:** If your brush or roller sleeve cannot be cleaned or reused, place it in your general waste bin. While recycling is important, bristles or roller sleeves with paint can cause issues at recycling canters, so it's best to dispose of them correctly.

Guidance for Disposing of Solvent-based Paint & Thinners

- 1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. **Use Paint Thinner::** Use a paint thinner to clean brushes and rollers.
- 3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
- 4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash.

VOC

- 4. EU limit value for this product (cat.: A/d): 300g/l (2010).This product contains max. 300g/lVOC. VOC content: High (25-50%).



SATINWOOD

Issued 10/2025

FURTHER SUPPORT

If you need further support, please contact the Dulux Technical Advice Centre on +353 21 422 0222

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the Dulux Technical Advice Centre or by visiting dulux.ie

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel