

Product dedicated for cleaning and degreasing of existing coatings, including thermoplastic acrylic finishes in order to remove residual grease, oil, wax, silicons, sand, etc. It is also suitable to degrease primers, surfacers and fillers prior to finishing.

**UNI DEGREASER****PROTECTION**

Use suitable respiratory protection. AkzoNobel Vehicle Refinishes recommends the use of a fresh air supply respirator.

BASIC RAW MATERIALS

A mixture of special solvents

SUITABLE FOR

Cleaning and degreasing of:
Bare steel
Galvanized steel
Aluminum
Plastic parts
Primers, surfacers and fillers
All existing coatings including thermoplastic acrylics

SURFACE PREPARATION

Wet a clean cloth thoroughly with Dynacoat Uni Degreaser and degrease/ clean the surface by rubbing steadily.
Immediately thereafter take a new clean cloth and rub the surface dry.

Note: to avoid condensation always use solvent borne degreasers at temperatures between 16 and 25°C

SHELF LIFE

4 years

VOC**2004/42/II B(a)(850)760**

The EU limit value for this product (product category: IIB.a) in ready to use form is max. 850 g/liter VOC.

The VOC content of this product in ready to use form is max. 760 g/liter.



TECHNICAL INFORMATION DYNACOAT UNI DEGREASER — D4.02.02

Akzo Nobel Car Refinishes B.V.
Address: Rijksstraatweg 31, PO Box 3, 2170 BA Sassenheim
Tel: +31(0)71308-6944

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

Akzo Nobel Car Refinishes B.V., PO Box 3, 2170 BA Sassenheim, The Netherlands. www.dynacoat.com