

Nordsjö Professional Sprutspackel (Spray filler)

December 2018

Product description

Nordsjö Professional Sprutspackel is a filler for spray application on ceilings and walls indoors in dry areas. Nordsjö Professional Sprutspackel was primarily designed for resurfacing using a sprayer on most types of walls and ceilings during repair and maintenance work, as well as new construction. Nordsjö Professional Sprutspackel is also suitable for grouting ceilings.

For resurfacing, it is recommended that a maximum thickness of 2 mm is applied. For filling individual holes and unevenness, up to 3 mm thickness is suitable.

Directions for use

Only apply to solid, clean and dry surfaces. When sanding, it is recommended that you wear eye protection and a dust mask. Do not apply filler when the temperature in room is below +5 °C.

Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet.

Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.



Technical data

Typical use: Interior

Binder: Copolymer latex

Particle size: Max 0.3 mm

Density: 1.75

Drying time 23°C 50% RH: 4 hours, depending on the thickness

Application temp: Min. +5°C

Humidity RH: 40-80% RF (65% RF is optimal)

Thinning: Water

Tools: Sprayer

Colour: White

Package sizes: 14L

Cleaning: Soapy water:

Storage: Frost-free

Spray equipment: Wagner 960, El-Myggen, Graco Mark X

Nozzle suggestions: Application 651-661. Grouting 655.

Meets the requirements for CE marking in accordance with EU Directive: EN 15824