

Nordsjö Professional Grov Sprutspackel (Filler)

March 2019



Product description

Nordsjö Professional Grov Sprutspackel is a very high coverage filler for use on surfaces where there are very high requirements on coverage. For use with a sprayer. Nordsjö Professional Grov Sprutspackel is suitable for filling holes and cracks, as well as resurfacing plaster, concrete and lightweight concrete in dry, interior spaces.

For resurfacing, it is recommended that a maximum thickness of 3 mm is applied. For filling individual holes and unevenness, up to 30 mm thickness is suitable.

Directions for use

Only apply to solid, clean and dry surfaces. Nordsjö Professional Grov Sprutspackel is applied using a sprayer and in thick layers, after which a final layer is applied using a filler with a finer grain.

Make sure that the filler has dried completely resurfacing or painting. When sanding, it is recommended that you wear eye protection and a dust mask.

Do not apply filler when the temperature in the room is below +5 °C.

Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.

Technical data

Typical use: Interior

Binder: Copolymer latex

Particle size: Max 0.40 mm

Density: 0.90

Drying time 23°C 50% RH: 4 hours, depending on the thickness

Application temp: Min +5°

Humidity RH: 40-80% RF (65% RF is optimal)

Thinning: Water

Tools: Sprayer

Package sizes: 14L

Sandability: May be lightly sanded

Colour: Grey tint

Storage: Frost-free

Spray equipment: Wagner 960, El-Myggan, Graco Mark X

Nozzle suggestions: Application 651-661

Meets the requirements for CE marking in accordance with EU Directive: EN 15824

Environment

This product meets the requirements for the Nordic Swan Ecolabel.

For more information: www.nordic-ecolabel.org

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website. AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009