

Nordsjö Professional Medium/LS 104 Sprutspackel (Spray filler)



June 2018

Product description

Nordsjö Professional Medium/LS 104 Sprutspackel is a universal, high coverage filler for spray application indoors, that has been specially designed for use in repair and maintenance work, as well as new construction. It is suitable for filling holes and cracks, as well as resurfacing plaster, concrete, lightweight concrete and drywall, wallpaper seams and painted surfaces (washed and sanded).

The composition of Nordsjö Professional Medium/LS 104 Sprutspackel also makes it suitable for affixing drywall tape in accordance with the requirements stated in HusAMA 18.

Directions for use

Only apply to solid, clean and dry surfaces. Nordsjö Professional Medium/LS 104 Sprutspackel is intended for spray application. Suitable spray equipment: Wagner 940 / 960, EI-Myggen, Graco Mark X

When sanding, it is recommended that you wear eye protection and a dust mask.

Store in a frost-free place.

Do not apply filler when the temperature in the room is below +5 °C.

Health and environment

When sanding or using a heat gun, hazardous dust and/or vapours may be released.

Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet.

Firmly reseal any opened cans. Remove filler from tools prior to cleaning. Immediately clean all tools after applying filler. Do not flush liquid filler residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.



Technical data

Typical use: Interior
Binder: Copolymer latex
Particle size: Max 0.16 mm
Density: 1.0
Drying time 23°C 50% RH: 4 hours, depending on the thickness
Filling depth: approx. 5 mm
Application temp: Min +5°
Humidity RH: 40-80% RF (65% RF is optimal)
Thinning: Water
Tools: Sprayer
Package sizes: 14L
Sandability: May be lightly sanded
Colour: Grey tint
Storage: Frost-free

Spray equipment: Wagner 940 / 960, EI-Myggen, Graco Mark X
Nozzle suggestions: Application 329-429, Drywall joint paper 229.

Meets the requirements for CE marking in accordance with EU Directive: EN 13963 & EN 15824

Environment

This product meets the requirements for the Nordic Swan Ecolabel.
For more information: www.nordic-ecolabel.org

AkzoNobel

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website.
AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009