

## WOOD PRIMER

**Dulux Trade** Wood Primer is a good, general purpose solvent-based primer suitable for internal and external use on all types of soft and hard woods. Wood that is highly resinous should be primed with **Dulux Trade** Aluminium Wood Primer.

### KEY BENEFITS

- Softwoods & Hardwoods
- For Interior & Exterior Use
- Helps Provide Excellent Adhesion

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on interior and exterior use on soft and hardwoods.

#### Pack Size

1L, 2.5L and 5L.

#### Colour Range

White.

#### Composition (nominal)

**Pigment:** Titanium Dioxide and Inert Mineral Extenders.

**Binder:** Oil Modified Alkyd.

**Solvent:** White Spirit.

#### Volume Solids

62% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease and wax.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Treat any knots in wood with an appropriate knotting solution.

Any surface defects should be filled with an appropriate **Polycell** Trade **Polyfilla**.

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable surface preparation, apply 1 coat of **Dulux Trade** Wood Primer to all bare wood and allow to dry. Finish with an appropriate **Dulux Trade** paint system.

### APPLICATION METHOD

Brush only. For Health & Safety reasons relating to all solvent-based paints, spray application is not recommended.

As with all solvent-based paints, do not apply at temperatures below 5°C (as recommended by British Standard BS 6150).

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 15m<sup>2</sup> per litre.

#### Spray Recommendations

This product should not be sprayed.

#### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 4-6 hours.

**Recoat:** 16-24 hours.

#### Responsible Cleaning

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

##### **Cleaning:**

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Use Paint Thinner:** Use a paint thinner to clean brushes and rollers.
3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any



Issued 08/25

## WOOD PRIMER

solvent-based paint, paint thinner or wash water down the drain or onto the ground.

***Do not flush paint down the drain, including when cleaning painting tools***

When this paint container is empty, please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/sustainability](https://duluxtrade.co.uk/sustainability).

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### **VOC**

EU limit value for this product (cat.: A/d): 300g/l (2010). This product contains max. 300g/l VOC. VOC content: High (25-50%).

### **Transportation & Storage**

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](https://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2023.