



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

ULTIMATE WOODSTAIN ROSEWOOD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ULTIMATE WOODSTAIN ROSEWOOD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Consumer use
Uses advised against
None

Product use : Solvent borne coating for exterior use.

1.3 Details of the supplier of the safety data sheet

ICI Paints AkzoNobel,
Wexham Road,
Slough,
Berkshire,
SL2 5DS, U.K.
Tel.: +44 (0) 333 222 70 70
www.duluxtrade.co.uk

e-mail address of person responsible for this SDS : duluxtrade.advice@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +44 (0)344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Date of issue/Date of revision : 3-4-2026

Version : 1

Date of previous issue : No previous validation

1/18

AkzoNobel

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

- Signal word** : No signal word.
- Hazard statements** : H412 - Harmful to aquatic life with long lasting effects.
- Precautionary statements**
- General** : P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.
- Prevention** : P273 - Avoid release to the environment.
- Response** : Not applicable.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Supplemental label elements** : Repeated exposure may cause skin dryness or cracking.
Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: -	≥20 - ≤25	Asp. Tox. 1, H304 EUH066	-	[1]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5	≤10	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	-	[1]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9	≤10	Asp. Tox. 1, H304 EUH066	-	[1]

SECTION 3: Composition/information on ingredients

Reaction mass of ethylbenzene and xylene	CAS: n/a REACH #: 01-2119488216-32 EC: 905-588-0	<1	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
3-iodo-2-propynyl butylcarbamate	REACH #: 01-2120762115-60 EC: 259-627-5 CAS: 55406-53-6	<0.25	Acute Tox. 4, H302 Acute Tox. 2, H330 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) (inhalation) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1056 mg/kg ATE [Inhalation (dusts and mists)] = 0.17 mg/l M [Acute] = 10 M [Chronic] = 10	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention.
- Inhalation

: Get medical attention if adverse health effects persist or are severe. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact

: Get medical attention if symptoms occur. Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion

: Get medical attention if adverse health effects persist or are severe. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a

SECTION 4: First aid measures

collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

SECTION 7: Handling and storage

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Reaction mass of ethylbenzene and xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-, p- or mixed isomers] Absorbed through skin STEL: 441 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours. STEL: 100 ppm 15 minutes.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	DNEL	Long term Inhalation	0.41 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	1.9 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m³	General population	Local
	DNEL	Long term Oral	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	300 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	640 mg/m³	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m³	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m³	Workers	Local
	DNEL	Short term Inhalation	1152 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	1286.4 mg/m³	Workers	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
Reaction mass of ethylbenzene and xylene	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic

SECTION 8: Exposure controls/personal protection

3-iodo-2-propynyl butylcarbamate	DNEL	Long term Inhalation	65.3 mg/m³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m³	General population	Local
	DNEL	Short term Inhalation	260 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	442 mg/m³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	0.023 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m³	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
propane-1,2-diol	Fresh water	260 mg/l	-
	Marine water	26 mg/l	-
	Sewage Treatment Plant	20000 mg/l	-
	Fresh water sediment	572 mg/l	-
	Marine water sediment	57.2 mg/l	-
neodecanoic acid, zirconium salt	Soil	50 mg/l	-
	Fresh water	0.14 mg/l	-
	Marine water	0.014 mg/l	-
	Fresh water sediment	0.78 mg/kg dwt	-
	Marine water sediment	0.078 mg/kg dwt	-
3-iodo-2-propynyl butylcarbamate	Soil	0.075 mg/kg dwt	-
	Secondary Poisoning	21 mg/kg	-
	Sewage Treatment Plant	0.44 mg/l	Assessment Factors
	Fresh water sediment	0.017 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.002 mg/kg dwt	Equilibrium Partitioning
manganese neodecanoate	Soil	0.005 mg/kg dwt	Assessment Factors
	Fresh water	85.3 µg/l	Assessment Factors
	Marine water	2.7 µg/l	Assessment Factors
	Sewage Treatment Plant	121.3 mg/l	Assessment Factors
	Fresh water sediment	230.6 mg/kg dwt	Assessment Factors
	Marine water sediment	23.06 mg/kg dwt	Assessment Factors
	Soil	167.33 mg/kg dwt	Assessment Factors

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state : Liquid.
- Color : Brown.
- Odor : Characteristic.
- Odor threshold : Not available.
- Melting point/freezing point : Not available.
- Boiling point or initial boiling point and boiling range : 149°C (300.2°F)
- Flammability : Not available.
- Lower and upper explosion limit : Greatest known range: Lower: 2.6% Upper: 12.6% (propane-1,2-diol)
- Flash point : Closed cup: 61°C (141.8°F) [Pensky-Martens]
- Auto-ignition temperature :

Ingredient name	°C	°F	Method
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	280 to 470	536 to 878	
propane-1,2-diol	371	699.8	

- Decomposition temperature : Not available.
- pH : Not applicable. [DIN EN 1262]
- Viscosity : Kinematic (room temperature): 4828 mm²/s [DIN EN ISO 3219]
Kinematic (40°C): 201 mm²/s [DIN EN ISO 3219]
- Solubility(ies) :

Media	Result
cold water	Not soluble [OECD (TG 105)]

- Partition coefficient: n-octanol/ water : Not applicable.

- Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	0.75 to 2.25	0.1 to 0.3				
propane-1,2-diol	0.15	0.02	EU A.4			

- Density : 0.932 g/cm³ [DIN EN ISO 2811-1]
- Vapor density : Not available.

Particle characteristics

- Median particle size : Not applicable.
- Percentage of particles with aerodynamic diameter ≤ 10 µm : 0
- Minimum ignition energy (mJ) : Not available.
- Fundamental burning velocity : Not applicable.

SECTION 9: Physical and chemical properties

SADT : Not available.
Heat of combustion : Not available.
Aerosol product
Type of aerosol : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : No specific data.
10.5 Incompatible materials : No specific data.
10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Vapor	Rat	8500 mg/m³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.68 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat - Female	1056 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	N/A	N/A	N/A	N/A	93.3
Reaction mass of ethylbenzene and xylene	N/A	1100	N/A	N/A	1.5
3-iodo-2-propynyl butylcarbamate	1056	N/A	N/A	N/A	0.17

Irritation/Corrosion

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Reaction mass of ethylbenzene and xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Cornea opacity	Rabbit	-	-	14 days
3-iodo-2-propynyl butylcarbamate	Eyes - Severe irritant	Rabbit	-	-	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl butylcarbamate	-	Experiment: In vitro Subject: Bacteria	Negative

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week

Conclusion/Summary : Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	-	Narcotic effects
Reaction mass of ethylbenzene and xylene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-
3-iodo-2-propynyl butylcarbamate	Category 1	inhalation	larynx

Aspiration hazard

SECTION 11: Toxicological information

Product/ingredient name	Result
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact : No known significant effects or critical hazards.
- Inhalation : No known significant effects or critical hazards.
- Skin contact : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact : No specific data.
- Inhalation : No specific data.
- Skin contact : Adverse symptoms may include the following:
 - irritation
 - dryness
 - cracking
- Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate	Sub-chronic NOAEL Dermal	Rat	200 mg/kg	90 days
	Sub-acute NOAEL Oral	Rabbit - Male, Female	13 mg/kg	-
	Chronic NOAEL Oral	Rat	20 mg/kg	2 years
	Sub-chronic NOAEL Oral	Rat	35 mg/kg	90 days
	Sub-chronic NOAEL Inhalation Vapor	Rat	1.16 mg/m³	90 days

- Conclusion/Summary : Not available.
- General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.

SECTION 11: Toxicological information

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Reaction mass of ethylbenzene and xylene 3-iodo-2-propynyl butylcarbamate	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 956 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.16 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 2920 ppb Marine water	Crustaceans - Neomysis mercedis - Adult	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 95 ppb Marine water	Fish - Oncorhynchus kisutch - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 100 ppb Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 72 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
3-iodo-2-propynyl butylcarbamate	OECD 310F	25 % - Readily - 28 days	1.03 gO ₂ /g	30 mg/l Activated sludge

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl butylcarbamate	-	-	Readily

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	10 to 2500	High
Reaction mass of ethylbenzene and xylene	3.12	8.1 to 25.9	Low

12.4 Mobility in soil

Soil/Water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

- 14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

- 14.7 Transport in bulk according to IMO instruments** : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

Other EU regulations

SECTION 15: Regulatory information

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (EU 2024/590)
Not listed.

Prior Informed Consent (PIC) (649/2012/EU)
Not listed.

Persistent Organic Pollutants
Not listed.

Seveso Directive
This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

Active substances

Ingredient name
3-iodo-2-propynyl butylcarbamate

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals
Not listed.

Montreal Protocol
Not listed.

Stockholm Convention on Persistent Organic Pollutants
Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)
Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals
Not listed.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

- Abbreviations and acronyms**
- : ATE = Acute Toxicity Estimate
 - CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 - DMEL = Derived Minimal Effect Level
 - DNEL = Derived No Effect Level
 - EUH statement = CLP-specific Hazard statement
 - N/A = Not available
 - PBT = Persistent, Bioaccumulative and Toxic
 - PNEC = Predicted No Effect Concentration
 - RRN = REACH Registration Number
 - SGG = Segregation Group
 - vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1

SECTION 16: Other information	
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 6-4-2026
Date of issue/ Date of revision : 3-4-2026
Date of previous issue : No previous validation
Version : 1
Unique ID : 27B82B9FCE311FE18BE98A390AFB1C8F

Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.