

SPRAYMATT

Dulux Trade Spraymatt is a spray specialised matt emulsion with high-opacity and a uniform flat matt finish. This specialised formulation can reduce overspray by up to 25%*. Suitable for all interior wall and ceiling surfaces, particularly new plaster and dry lining. **Dulux Trade Spraymatt** is 99.9% VOC Free**, to minimise the impact on indoor air quality.***

*Compared to Supermatt White. ** Based on in-can VOC content, measured in accordance with ISO 11890-2:2020. *** Independently tested for emissions, including formaldehyde, TVOC, TSVOC and Cat 1A & 1B carcinogens.

Accreditations

BREEAM Compliant	LEED Compliant	WELL Compliant	EPD Available	Reaction to Fire EN 13501-1
✓	✓	✓	✓	✓

This product has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which is based on ISO 16000 / EN 16516, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 2018 & LEED v4.1 compliant and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. For further information please visit the 'Datasheets and Documents' section of the specific product page at duluxtrade.co.uk

KEY BENEFITS

- Spray Specialised Formula
- Up to 25% reduced overspray
- Ideal for new plaster and dry lining

PRODUCT INFORMATION

Typical Use

Ideal for use on plaster that is still drying out and dry-lining. Also suitable for use on all normal interior wall and ceiling surfaces.

Pack Size

10L only.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk

Film Properties

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces such as radiators.

Water Resistance: Where frequent heavy condensation is likely, such as some kitchens and bathrooms, **Dulux Trade** Diamond Eggshell is more suitable.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: PVA Copolymer Emulsion.

Solvent: Water.

Volume Solids

White: 30% (nominal), other colours will vary.

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry. If necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Suitable for painting over skimmed plaster after 24-48 hours. A good visual test to the suitability of the plaster to be painted is when it has started to turn from wet brown to dry pink plaster.

The normal finishing process is 2 full coats of Dulux Trade Spraymatt, however for significant colour change additional coats may be required.

SPRAYMATT

Thinning is not usually required but may be thinned up to 1 part clean water to 10 parts paint under normal conditions if desired, or up to 1 part clean water to 5 parts paint when applying over a porous substrate.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller and airless spray.

As with other water-based paints, do not apply in temperatures below 8°C (as recommended by British Standard BS 6150).

To minimise picture framing or patchy finishes, we strongly recommend stirring the paint thoroughly prior to use. If thinned, the paint used for cutting-in and for rolling should be to the same ratio. Cut in one wall at a time, then rolling immediately afterwards, not allowing the cutting-in to dry prior to rolling. Cut in no more than 5 to 8cm away from any internal angles, including sockets/switches, skirting, architraves, etc. Roll into the cutting-in, ensuring you roll as close to the edge as possible.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre on sealed surfaces.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.

Airless spray application: Thinning not usually required but can add up to 1 part clean water to 5 parts paint.

Spray Recommendations

Airless Spray: For best results use a 517 Low Pressure tip @ 1400 – 1800 psi (97 – 124 bar). Alternatively, use a 517 tip @ 2100 – 2500 psi (145 - 172 bar).

Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

- 1. Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
- 3. Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
- 4. Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
- 5. Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
- 6. Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty, please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

Ready Mixed: This product contains max. 0.9g/l VOC. VOC content: Trace (0-0.1%).



Issued 09/25

1029

SPRAYMATT

Tinted Colour: This product contains max. 0.9g/l
VOC. VOC content: Trace (0-0.1%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla and;Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2024.