

SUPER GRIP PRIMER

Dulux Trade Super Grip Primer is a water-based single pack primer formulated to provide good adhesion for subsequent coats of paint when applied to difficult substrates. Typical substrates include ceramic tiles, melamine, glass, anodised aluminium, aged gloss paint, stove enamel, and powder-coated metal. When using **Dulux Trade Super Grip Primer** over melamine or powder-coated metal, light abrading of the surface is recommended before application of primer. This product is recommended for interior and exterior use.

Accreditations

BREEAM Compliant	LEED Compliant	WELL Compliant
✓	✓	✓

This product has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which is based on ISO 16000 / EN 16516, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 2018 & LEED v4.1 compliant and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. For further information please visit the 'Datasheets and Documents' section of the specific product page at duluxtrade.co.uk

KEY BENEFITS

- Water-Based
- For Surfaces Such as Ceramic Tiles, Laminates, Glass
- Provides Good Adhesion on Problem Surfaces

PRODUCT INFORMATION

Typical Use

Suitable for use on interior and exterior use on difficult substrates.

Pack Size

1L, 2.5L and 5L.

Colour Range

White only.

Composition (nominal)

Pigment: Titanium dioxide & inert extenders.

Binder: Water-based emulsion.

Solvent: Water.

Volume Solids

37% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all

defective or poorly adhering material such as efflorescence, dirt, grease or wax.

Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. When used over laminates or powder-coated metal, these substrates should first be lightly abraded before the application of **Dulux Trade Super Grip Primer**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable preparation, apply one coat of **Dulux Trade Super Grip Primer**, followed by the appropriate **Dulux Trade** paint system.

NOTE: In areas where there is direct water contact (such as shower enclosures) or where frequent or heavy condensation is likely, a solvent-based finish must be used. If in doubt, contact the **AkzoNobel** Technical Advice Centre for further advice.

APPLICATION METHOD

Brush, short-pile roller or airless sprays.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

SUPER GRIP PRIMER

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 18m² per litre.

Thinning

Normal use: This product does not require thinning for brush, roller or airless spray application.

Airless spray application: Thinning not required.

Spray Recommendations

Airless Spray: Satisfactory through most equipment. The use of an FF fine spray tip is recommended.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4-6 hours.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

- 1. Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.

- 3. Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
- 4. Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
- 5. Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
- 6. Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/i): 140g/l (2010). This product contains max. 30g/l VOC. VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 309) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2025.