

ULTRA GRIP PRIMER

Dulux Trade Ultra Grip Primer is a water-based two-pack primer formulated to provide excellent adhesion for subsequent coats of paint, when applied to difficult substrates such as glazed ceramic wall tiles, laminates, glass, anodised aluminium, powder-coated steel and stove enamel surfaces. Suitable for interior and exterior use. Compatible with **Dulux Trade** paint systems.

KEY BENEFITS

- Two-Pack Primer
- For Stove Enamels, Laminates, Glass
- Excellent Adhesion on Problem Surfaces

PRODUCT INFORMATION

Typical Use

Suitable for use on interior and exterior use on difficult substrates.

Pack Size

0.8L Base and 0.2L Activator (1L when mixed).

Colour Range

Matt White.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 100 microns.

Dry: 45 microns.

Composition (nominal)

Pigment: Non-lead pigments.

Binder: Epoxy resin.

Solvent: Water.

Volume Solids

45%.

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, and dry (new surfaces particularly must be fully dry) and free from all loose or powdery material using a stiff fibre brush. Where necessary, thoroughly degrease, followed by rinsing with fresh, clean water.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint-free cloth. Special

precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Spot prime bare metal and metal fixings with 1 coat of **Dulux Trade Metalshield** Zinc Phosphate Primer.

It is recommended that a small test area is applied before treating the entire surface to ensure compatibility.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Apply 1 coat of **Dulux Trade** Ultra Grip Primer, and then finish with an appropriate **Dulux Trade** paint system.

Mixing Ratio: supplied in correct proportions. Add all of the Activator to the Base container and mix thoroughly for at least 5 minutes, until the product is smooth and even. Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration.

Pot life: up to 2 hours at 20°C.

APPLICATION METHOD

Brush or short pile roller only. Do not spray.

As with all water based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 10m² per litre (at a dry film thickness of 45 microns).

Thinning

Ready to use when mixed. If required, add a maximum of 1 part clean water to 10 parts activated paint.

Spray Recommendations

This product should not be sprayed.

ULTRA GRIP PRIMER

Drying Times

Single coat at standard thickness:

Touch Dry: At 20°C – 4 -6 hours.

Recoat: Minimum of 16 hours and maximum of 7 days. Hard dry after 16 hours. Recoat before 7 days for optimum intercoat adhesion.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

- 1. Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
- 3. Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
- 4. Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
- 5. Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container.

Once settled, pour the clear water into another container for reuse or disposal.

- 6. Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty, please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/j): 140g/l (2010). This product contains max. 2 g/l VOC. VOC content: Minimal (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS308) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Metalshield and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2025.