

## ALKALI RESISTING PRIMER

**Dulux Trade** Alkali Resisting Primer is a solvent-based primer particularly suitable for use on well-ventilated interior and exterior masonry surfaces, including plaster, that may contain alkalis. It is also highly recommended for its outstanding stain-sealing properties treated with fire retardant chemicals.

### KEY BENEFITS

- Plaster & Masonry Surfaces
- Seals Fresh, Alkaline Surfaces
- Blocks Stains such as Nicotine & Fire Damage
- Outstanding Stain-sealing properties

### PRODUCT INFORMATION

#### Typical Use

Interior and exterior masonry surfaces that may contain alkalis.

#### Pack Size

5L.

#### Colour Range

Off-white.

#### Composition (nominal)

**Pigment:** Titanium Dioxide,

**Binder:** Acrylic Copolymer.

**Solvent:** White Spirit.

#### Volume Solids

44% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as efflorescence, dirt, grease or wax. Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable surface preparation, apply 1 coat of **Dulux Trade** Alkali Resisting Primer to bare or stained surfaces. Finish with an appropriate **Dulux Trade** paint system.

### APPLICATION METHOD

Brush only.

As with all solvent based paints (according to British Standard BS 6150), do not use in temperatures below 5°C.

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 9m<sup>2</sup> per litre.

#### Spray Recommendations

For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

#### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 6-10 hours.

**Recoat:** 16-24 hours.

#### Responsible Cleaning

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

##### **Cleaning:**

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Use Paint Thinner:** Use a paint thinner to clean brushes and rollers.
3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a



## ALKALI RESISTING PRIMER

hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash water down the drain or onto the ground.

***Do not flush paint down the drain, including when cleaning painting tools***

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/sustainability](https://duluxtrade.co.uk/sustainability)

### **Transportation & Storage**

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### **VOC**

EU limit value for this product (cat : A/h): 750g/l (2010). This product contains max. 475g/l VOC. VOC Content: High (25-50%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre, or visiting [duluxtrade.co.uk](https://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Florish logo, Dulux Trade, and Community RePaint are all trademarks of the AkzoNobel group. © AkzoNobel 2024.