

## QUICK DRY VARNISH

**Dulux Trade Quick Dry Varnish** is a water-based interior varnish which gives a tough and durable finish. It can be used over bare wood and previously stained or varnished surfaces. Rapid drying properties allow work to be completed quickly.

BREEAM Compliant	LEED Compliant	WELL Compliant*	EPD Available
✓		✓	✓

This product has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which is based on ISO 16000 / EN 16516, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 2018 compliant and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. For further information please visit the 'Datasheets and Documents' section of the specific product page at [duluxtrade.co.uk](http://duluxtrade.co.uk)

\*Gloss finish only

### KEY BENEFITS

- Recoat in only 2 Hours
- Doors, Trim, Furniture and Joinery
- Water-Based

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on interior wood, veneer, cork and chipboard.

#### Pack Size

1L and 2.5L.

#### Colour Range

Clear Gloss or Satin and colours (in Satin only – see appropriate **Dulux Trade** colour literature or visit [duluxtrade.co.uk](http://duluxtrade.co.uk)).

#### Composition (nominal)

**Pigment:** Inert Matting Agents.

**Binder:** Acrylic Copolymer Emulsion

**Solvent:** Water.

#### Volume Solids

27% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax.

Remove any defective or poorly adhering varnish. Special precautions should be taken during surface

preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

When applying to previously stained or varnished surfaces, rub down thoroughly along the grain of the wood to provide a 'key'. Use 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

New or bare surfaces must also be rubbed down with a suitable grade of abrasive paper and dusted off (refer to your COSHH Assessment).

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE AND DURING USE. Apply 2 or 3 coats of Dulux Trade Quick Dry Varnish. For best results lightly sand down with a fine grade abrasive paper, along the grain of the wood between coats of varnish. Then wipe off with a damp, lint free cloth. Avoid the inhalation of dust and wear a suitable face mask if dry sanding.

**Dulux Trade** Quick Dry Varnish can be used over previously stained wood to vary sheen level i.e. gloss/satin.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

### APPLICATION METHOD

Brush or roller only. Do not spray. For best results, use a good quality synthetic (nylon polyester) brush, designed for use with water-based paints, stains and varnishes. Brush out evenly, taking care to avoid overlaps and finish along the grain.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).



## QUICK DRY VARNISH

### Practical Coverage

On smooth surfaces of average porosity, a guide to the practical coverage is up to 20m<sup>2</sup> per litre.

### Thinning

Do not thin this product.

### Spray Recommendations

This product is not suitable for spray application.

### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 30 minutes.

**Recoat:** 2 hours.

### Responsible Cleaning

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

#### **Cleaning:**

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
3. **Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.

4. **Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
5. **Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
6. **Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

#### ***Do not flush paint down the drain, including when cleaning painting tools***

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/sustainability](https://duluxtrade.co.uk/sustainability)

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/e): 130g/l (2010). This product contains max. 78 g/l VOC. VOC content: Low (0.30-7.99%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

**Always read full Health, Safety & Environmental Information on can before use.**

Safety Datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](https://duluxtrade.co.uk)

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, and Community RePaint are trademarks of the AkzoNobel group.  
© AkzoNobel 2025.