



**Environmental
Product
Declaration**

According to ISO14025+EN15804+A2

This declaration is for:
Armstead Trade Durable Matt

Provided by:
AkzoNobel Decorative Paints



MRPI® registration:
1.1.01001.2025

Program operator:
Stichting MRPI®
Publisher:
Stichting MRPI®
www.mrpi.nl

Date of first issue:
8-10-2025
Date of this issue:
8-10-2025
Expiry date:
8-10-2030





COMPANY INFORMATION

AkzoNobel Decorative Paints
Wexham Road
SL2 5DS
Slough
United Kingdom
+44 (0)333 222 70 70

<https://www.akzonobel.com>

MRPI® REGISTRATION

1.1.01001.2025

DATE OF THIS ISSUE

8-10-2025

EXPIRY DATE

8-10-2030

SCOPE OF DECLARATION

This MRPI®-EPD certificate is verified by Gert-Jan Vroege, Eco-Intelligence. The LCA study has been done by Brienne Wiersema & Gudo Wisselo, Ecomatters B.V. The certificate is based on an LCA-dossier according to ISO14025+EN15804+A2. It is verified according to the 'Verification protocol for MRPI LCA project report & EPD 21th of May 2025, V. 5.2'. EPDs of construction products may not be comparable if they do not comply with EN15804+A2. Declaration of SVHC that are listed on the 'Candidate list of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.

PROGRAM OPERATOR

Stichting MRPI®
Kingsfordweg 151
1043 GR
Amsterdam

PRODUCT

Armstead Trade Durable Matt


DECLARED UNIT / FUNCTIONAL UNIT

1 Area (m2)

DESCRIPTION OF PRODUCT

Armstead Trade Durable Matt is a professional quality, tough and durable matt finish that is ideal for high traffic areas. It is scrubbable and offers good stain resistance. Suitable for all normal interior wall surfaces.

VISUAL PRODUCT



MORE INFORMATION

<https://www.armstead.co.uk/en/products/armstead-trade-durable-matt?size=2.5L>

Ing. L. L. Oosterveen MSc. MBA Managing Director MRPI	DEMONSTRATION OF VERIFICATION
	CEN standard EN15804 serves as the core PCR [1]
	Independent verification of the declaration and data according to ISO14025+EN15804+A2
	Internal: External: X
	Third party verifier: Gert-Jan Vroege, Eco-Intelligence
	[1] PCR = Product Category Rules





DETAILED PRODUCT DESCRIPTION

Armstead Trade Durable Matt is a professional quality, tough and durable matt finish that is ideal for high traffic areas. It is scrubbable and offers good stain resistance. Suitable for all normal interior wall surfaces.

Typical Use

Suitable for all normal interior wall surfaces.

Application Method

Brush, roller and airless spray. As with other water-based paints, do not apply in temperatures below 8°C (as recommended by British Standard BS 6150).

Pack Size

2.5L, 5L, 10L

Production process and conditions of delivery

During paint production, the raw materials are pre-weighed according to the percentage of each in the formulation. The pigment is then dispersed in a mixture of binder and solvent using a variety of machines. The amount and type of dispersion is product specific and depends on the type of finish required. Finally, tinter is added to correct the colour, the paint is thinned to viscosity, filtered and filled into the appropriate packaging container. All paint containers are transported from the production sites to a distribution center and finally to the customers in the UK.

Paint characteristics		Unit
Waterborne / Solventborne	Waterborne	value
Interior wall / Exterior wall / Trim	Interior Wall	value
Lifetime	4	years
Density	1,4	kg/L
Coverage	14	m2/L
Number of layers	1	value
VOC content	5,82	g/L paint

Component (> 1%)	(kg / %)
Pigment - Lightfast pigments	Confidential
Binder - Acrylic copolymer	Confidential
Solvent - Water	Confidential

SCOPE AND TYPE

The type of this EPD is Cradle-to-Gate with options. All major steps from the extraction of natural resources to the final disposal of the product are included in the environmental performance of the manufacturing phase, except those that are not relevant to the environmental performance of the product. This declaration does not imply an indicator result of zero.

This EPD is representative for products produced in the United Kingdom. The application market is for customers in the United Kingdom and Ireland. Likewise, for the end-of-life, the fate of the paint product is described within the same context.

The software LCA for Experts 10.9.1.17 Professional is used to perform the LCA. In the model, the Ecoinvent 3.11 database was used.

The validity of this EPD is in correspondence with the specifications of the LCA project report.

All impacts associated with the upstream production of materials and energy are included in the system boundaries. Mining activities and controlled landfills are included in the product systems. The emissions and resource extractions derived from these processes are considered elementary exchanges between the product systems and the environment.






PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport gate to site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse - Recovery - Recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X

X = Modules Assessed

ND = Not Declared



REPRESENTATIVENESS

This EPD is representative for the following paint products belonging to the Armstead Trade Durable Matt paint group:

1. Armstead Trade Durable Matt White
2. Armstead Trade Durable Matt Magnolia
3. Armstead Trade Durable Matt Pastel
4. Armstead Trade Durable Matt Mid Base
5. Armstead Trade Durable Matt Strong Base

This EPD is representative for the products manufactured in Ashington and Stowmarket, both UK, and sold in the UK and Ireland.



ENVIRONMENTAL IMPACT per functional unit or declared unit (core indicators A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-total	kg CO2 eq.	1,34E-01	5,31E-03	2,58E-02	1,65E-01	9,00E-03	2,04E-02	ND	0,00E+00	4,60E-04	0,00E+00	2,03E-02	-6,89E-03						
GWP-fossil	kg CO2 eq.	1,33E-01	5,30E-03	2,51E-02	1,64E-01	8,99E-03	2,00E-02	ND	0,00E+00	4,60E-04	0,00E+00	2,03E-02	-6,84E-03						
GWP-biogenic	kg CO2 eq.	-7,66E-05	3,26E-06	6,13E-04	5,40E-04	5,53E-06	3,95E-04	ND	0,00E+00	2,83E-07	0,00E+00	2,88E-06	-4,55E-05						
GWP-luluc	kg CO2 eq.	4,75E-04	1,92E-06	2,73E-05	5,04E-04	3,25E-06	8,74E-07	ND	0,00E+00	1,66E-07	0,00E+00	3,37E-07	-5,54E-06						
ODP	kg CFC11 eq.	1,27E-08	1,17E-10	5,53E-10	1,34E-08	1,98E-10	1,46E-11	ND	0,00E+00	1,01E-11	0,00E+00	1,89E-11	-2,01E-10						
AP	mol H+ eq.	9,19E-04	2,16E-05	1,26E-04	1,07E-03	3,67E-05	5,46E-06	ND	0,00E+00	1,88E-06	0,00E+00	4,94E-06	-2,01E-05						
EP-fresh water	kg PO4 eq.	3,65E-05	3,77E-07	8,44E-06	4,53E-05	6,38E-07	9,60E-07	ND	0,00E+00	3,27E-08	0,00E+00	7,64E-08	-2,09E-06						
EP-marine	kg N eq.	1,34E-04	8,13E-06	2,55E-05	1,68E-04	1,38E-05	1,38E-05	ND	0,00E+00	7,06E-07	0,00E+00	2,03E-06	-4,43E-06						
EP-terrestrial	mol N eq.	1,41E-03	8,82E-05	2,67E-04	1,77E-03	1,50E-04	2,19E-05	ND	0,00E+00	7,65E-06	0,00E+00	2,20E-05	-4,38E-05						
POCP	kg NMVOC eq.	4,86E-04	3,34E-05	1,03E-04	6,23E-04	5,66E-05	4,40E-04	ND	0,00E+00	2,90E-06	0,00E+00	8,18E-06	-2,23E-05						
ADP-minerals & metals	kg Sb eq.	7,16E-07	1,50E-08	6,21E-07	1,35E-06	2,54E-08	4,16E-09	ND	0,00E+00	1,30E-09	0,00E+00	1,26E-09	-1,48E-08						
ADP-fossil	MJ, net calorific value	2,31E+00	7,83E-02	4,37E-01	2,83E+00	1,33E-01	1,24E-02	ND	0,00E+00	6,79E-03	0,00E+00	1,32E-02	-1,51E-01						
WDP	m3 world Deprived	4,68E+00	4,67E-04	1,33E-02	4,69E+00	7,92E-04	-2,80E-02	ND	0,00E+00	4,05E-05	0,00E+00	-4,64E-03	-1,49E-03						

- GWP-total = Global Warming Potential total
- GWP-fossil = Global Warming Potential fossil fuels
- GWP-biogenic = Global Warming Potential biogenictotal
- GWP-luluc = Global Warming Potential land use and land use change
- ODP = Depletion potential of the stratospheric ozone layer
- AP = Acidification Potential, Accumulated Exceedence
- EP-freshwater = Eutrophication Potential, fraction of nutrients reaching freshwater end compartment
- EP-marine = Eutrophication Potential, fraction of nutrients reaching marine end compartment
- EP-terrestrial = Eutrophication Potential, Accumulated Exceedence
- POCP = Formation potential of tropospheric ozone photochemical oxidants
- ADP-minerals & metals = Abiotic Depletion Potential for non-fossil resources [1]
- ADP-fossil = Abiotic Depletion for fossil resources potential [1]
- WDP = Water (user) deprivation potential, deprivation-weighted water consumption [1]

Disclaimer [1]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.



ENVIRONMENTAL IMPACT per functional unit or declared unit (additional indicators A2)

Unit		A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PM	Disease incidence	8,47E-09	4,25E-10	1,49E-09	1,04E-08	7,20E-10	1,12E-10	ND	0,00E+00	3,69E-11	0,00E+00	9,16E-11	-2,36E-10						
IRP	kBq U235 eq.	1,20E-02	8,75E-05	2,33E-03	1,44E-02	1,48E-04	6,33E-05	ND	0,00E+00	7,59E-06	0,00E+00	1,57E-05	-1,06E-03						
ETP-fw	CTUe	1,42E+00	9,06E-03	1,31E-01	1,56E+00	1,54E-02	1,35E-01	ND	0,00E+00	7,86E-04	0,00E+00	1,88E+00	-1,37E-02						
HTP-c	CTUh	1,15E-10	9,29E-13	3,60E-10	4,77E-10	1,58E-12	2,54E-11	ND	0,00E+00	8,06E-14	0,00E+00	2,09E-11	-3,23E-12						
HTP-nc	CTUh	1,48E-09	4,26E-11	4,64E-10	1,99E-09	7,23E-11	1,62E-10	ND	0,00E+00	3,70E-12	0,00E+00	2,01E-10	-2,87E-11						
SQP	-	7,02E-01	7,85E-02	2,61E-01	1,04E+00	1,33E-01	1,21E-02	ND	0,00E+00	6,81E-03	0,00E+00	2,82E-02	-1,34E-02						

- PM = Potential incidence of disease due to PM emissions
- IRP = Potential Human exposure efficiency relative to U235 [1]
- ETP-fw = Potential Comparative Toxic Unit for ecosystems [2]
- HTP-c = Potential Comparative Toxic Unit for humans, cancer [2]
- HTP-nc = Potential Comparative Toxic Unit for humans, non-cancer [2]
- SQP = Potential soil quality index [2]

Disclaimer [1]:

- This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste.

Disclaimer [2]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.





OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit (A1 en A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg	0,00E+00	0,00E+00	1,84E-04	1,84E-04	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
NHWD	kg	0,00E+00	0,00E+00	1,08E-03	1,08E-03	0,00E+00	1,39E-02	ND	0,00E+00	0,00E+00	0,00E+00	5,48E-02	0,00E+00						
RWD	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
MFR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,20E-03	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
MER	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,06E-03	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
EEE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	8,11E-03	ND	0,00E+00	0,00E+00	0,00E+00	6,64E-03	0,00E+00						
ETE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,67E-02	ND	0,00E+00	0,00E+00	0,00E+00	1,42E-02	0,00E+00						

- HWD = Hazardous Waste Disposed
- NHWD = Non Hazardous Waste Disposed
- RWD = Radioactive Waste Disposed
- CRU = Components for reuse
- MFR = Materials for recycling
- MER = Materials for energy recovery
- EEE = Exported Electrical Energy
- ETE = Exported Thermal Energy



RESOURCE USE per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	7,68E-02	1,21E-03	1,09E-01	1,88E-01	2,05E-03	7,05E-04	ND	0,00E+00	1,05E-04	0,00E+00	2,16E-04	-8,95E-03						
PERM	MJ	2,42E-07	1,82E-10	4,84E-09	2,47E-07	3,09E-10	2,53E-10	ND	0,00E+00	1,58E-11	0,00E+00	9,65E-11	-4,30E-10						
PERT	MJ	7,68E-02	1,21E-03	1,09E-01	1,88E-01	2,05E-03	7,05E-04	ND	0,00E+00	1,05E-04	0,00E+00	2,16E-04	-8,95E-03						
PENRE	MJ	2,31E+00	7,83E-02	4,37E-01	2,83E+00	1,33E-01	1,24E-02	ND	0,00E+00	6,79E-03	0,00E+00	1,32E-02	-1,51E-01						
PENRM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
PENRT	MJ	2,31E+00	7,83E-02	4,37E-01	2,83E+00	1,33E-01	1,24E-02	ND	0,00E+00	6,79E-03	0,00E+00	1,32E-02	-1,51E-01						
SM	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
NSRF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
FW	m3	1,67E-01	1,09E-05	3,11E-04	1,67E-01	1,84E-05	-6,52E-04	ND	0,00E+00	9,44E-07	0,00E+00	-1,08E-04	-3,46E-05						

- PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials
- PERM = Use of renewable primary energy resources used as raw materials
- PERT = Total use of renewable primary energy resources
- PENRE = Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials
- PENRM = Use of non-renewable primary energy resources used as raw materials
- PENRT = Total use of non-renewable primary energy resources
- SM = Use of secondary materials
- RSF = Use of renewable secondary fuels
- NSRF = Use of non-renewable secondary fuels
- FW = Use of net fresh water

BIOGENIC CARBON CONTENT per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
BBCpr	kg C	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
BCCpa	kg C	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						

- BCCpr = Biogenic carbon content in product
- BCCpa = Biogenic carbon content in packaging



CALCULATION RULES

Cut off criteria

Some cut-offs were applied to the study. During the manufacturing process, the input of consumables and disposed packaging from the raw materials is cut off from the system boundaries due to lack of data on the composition of waste. Furthermore, brushes, clothes, buckets etc. used during the application process are excluded from the assessment since they are considered capital goods. Additionally, the energy consumed during application, used for instance in spray applicators, has not been included due to its insignificance.

Data quality and data collection period

Specific data was collected from AkzoNobel through a questionnaire, including inquiries about paint characteristics and packaging, production information and end-of-life. The data collection period for specific data was the year 2024. Data gaps (i.e. some transport data, end of life scenarios) were covered with data generic values for transport as described in the Product Environmental Footprint Category Rules - Decorative Paints document version 1.0 published by CEPE and reviewed in April 2018 and the Product Environmental Footprint method (European Commission, 2021). Generic data (i.e. upstream acquisition and production of raw materials, transport, waste treatment processes) was selected from Ecoinvent 3.11 database. In the case of missing data, a relevant proxy was searched and adjusted to the corresponding unit process.

Allocation procedure

To allocate the emissions and inputs to the manufactured products, the decision-hierarchy in ISO 14044 is used (ISO 2006). It is not possible to sub-divide the site data into a more detailed level or find physical causalities between inputs and outputs, thus allocation is done based on mass, considering the annual production of paint product for each site. The production of paint comprises only of the mixing ingredients. Therefore, the environmental impact is expected to be related to the mass of the products.

SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

A1. Raw materials supply

This module considers the extraction and processing of all raw materials and energy which occur upstream to the manufacturing process, as well as waste processing up to the end-of waste state.

A2. Transport of raw materials to manufacturer

This includes the transport distance of the raw materials to the manufacturing facility via road. As no primary data was available for the transportation distances, the default values from the PEFCR for Decorative Paints were used.

Transport of raw materials		unit
Distance for raw materials	460	km
Distance for packaging materials	250	km
Capacity	> 32 t, 64% payload	value

A3. Manufacturing

This module covers manufacturing and includes all processes linked to production such as storing, mixing, packing and internal transportation. Use of electricity, fuels and auxiliary materials in paint production is accounted for.

Data regarding paint production was provided for the manufacturing site where the AM Durable Matt paints are produced in Ashington, UK. Primary data and site-specific data was provided for the consumption of utilities and product packaging. The electricity is modelled as 100% renewable using a renewable supply mix. For upstream (raw material processes) and downstream processes (application, use, and waste processing) generic data is used when no specific data was available.

The manufacture of production equipment and infrastructure is not included in the system boundary.

A4. Transport to Regional Distribution Centre and customer

All paint containers are transported from the production facility into a distribution centre and then finally to the customer. As no primary data was available for the transportation distances, the default values from the PEFCR for Decorative Paints were used.





Transport to RDC and PoS		unit
Factory to Regional Distribution Centre	350	km
Regional Distribution Centre to Point of Sale	370	km
Capacity	> 32 t, 64% payload	value

A5. Application and use

This module includes the environmental aspects and impacts associated with the application and of the paint. It is assumed that no energy is required during the application of this paint. The use of paintbrushes and other appliances used during application are not included. There are some raw materials added in the paint formulations which contain small amounts of solvents. The VOC emissions during application of paint are included in this module.

C2. Transport to incineration

This module includes one-way transportation distance of the demolition or sorting site to the dump site. As no primary data was available for the transportation distances, the default values from the PEFCR for Decorative Paints were used.

Transport of EoL waste		unit
Distance for raw materials	80	km
Capacity	> 32 t, 64% payload	value

C3. Waste processing and C4. Disposal

The end of life stage is encompassed in these modules. It is assumed that the paint is used as exterior paint and that part of the paint is lost during application. The applied paint is then disposed of with the substrate on which it has been applied.

EoL		unit
Landfill	88	%
Incineration with energy recovery	12	%





DECLARATION OF SVHC

None of the substances contained in the product are listed in the "Candidate List of Substances of Very High Concern for authorisation", or they do not exceed the threshold with the European Chemicals Agency.

REFERENCES

- CEPE, Raw materials LCI database for the European Council of the Paint, Printing Ink and Artists' Colours Industry (CEPE), version 4.0, IVL Swedish Environmental Research Institute, 2024
- EN 15804:2012+A2:2019 Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products, of 2019.
- European Commission, (2021). Annex II: Product Environmental Footprint Method. In Environmental Footprint Guidance Document. [Online] Available at: https://environment.ec.europa.eu/document/download/680503dc-5a19-4f6a-bb92-84d9bfc8f312_en?filename=Annexes%201%20to%202.pdf
- ISO 14040/14044 on Life Cycle Assessments
- Product Environmental Footprint Category Rules - Decorative Paints version 1.0, 2018. Developed by the Technical Secretariat Decorative Paints of the European Council of the Paint, Printing Ink and Artists' Colours Industry.
- Product Environmental Footprint Category Rules Guidance - Guidance for the 13 development of Product Environmental Footprint Category Rules (PEFCRs), version 6.3, 2017. Developed by the European Commission.
- Sanséau-Blanchard, A, 2024. Personal communication with Ana Sanséau -Blanchard, Product Sustainability Manager, Akzo Nobel Industrial Coatings, UK
- Sphera GaBi Software-System and Database for Life Cycle Engineering. Copyright 1992-2018 Sphera.
- UK statistics on waste. (2025, July 23). GOV.UK. <https://www.gov.uk/government/statistics/uk-waste-data/uk-statistics-on-waste>
- Wernet, G., Bauer, C., Steubing, B., Reinhard, J., Moreno-Ruiz, E., and Weidema, B., 2016. The ecoinvent database version 3 (part I): overview and methodology. The International Journal of Life Cycle Assessment, [online] 21(9), pp.1218–1230. Available at: <<http://link.springer.com/10.1007/s11367-016-1087-8>> [Accessed 20-01-2021]

REMARKS

None

