

ULTRA MATT MULTI-SURFACE

Dulux Trade Ultra Matt Multi-surface is specially formulated to provide a dead matt, non-reflective finish and is ideal for areas of critical lighting. Designed for direct application and eliminating the need for a primer. It has strong adhesion to plaster, drylining, galvanised steel, aluminium, wood, PVC, ferrous metal and copper.

Full coverage in a single coat with spray application makes it perfectly suited for large commercial ceilings.

KEY BENEFITS

- Dead Matt Finish
- Suitable For Spray Application
- Self-Priming
- Strong Adhesion To Multi-Surfaces

PRODUCT INFORMATION

Typical Use

Suitable for use on plaster, drylining, galvanised steel, aluminium, wood, PVC, ferrous metal and copper.

Pack Size

10L

Colour Range

Black - Ready Mixed

Composition (nominal)

Pigment: Titanium dioxide, zinc oxide & inert extenders.

Binder: Water-based emulsion.

Solvent: Water.

Volume Solids

43% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as efflorescence, dirt, grease or wax.

Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

SYSTEMS INFORMATION

The normal finishing process is one coat. Under certain conditions, 2 coats might be needed when applying over a porous surface.

APPLICATION METHOD

Spray, brush and roller.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Thinning is not usually required but can be diluted up to 1 part of clean water to 20 parts of paint.

Spray Recommendations

Airless Spray: For best results use a 515 or 517 Low Pressure tip @ 1300 - 1700 psi (89 – 117 bar).

Alternatively, use a 517 tip @ 2000 – 2400 psi (138 - 165 bar).

Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4 hours.

ULTRA MATT MULTI-SURFACE

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

- 1. Remove Excess Paint:** Scrape off excess paint into container for future projects.
- 2. Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
- 3. Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
- 4. Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
- 5. Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
- 6. Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/h): 30g/l (2010). This product contains max. 0.9 g/l VOC. VOC content: Trace (<0.1%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2024.