

## ULTRA MATT

Ideal for ceilings, **Dulux Trade Ultra Matt** has been formulated to be anti-flashing and provide a dead matt, non-reflective finish at all angles. It has excellent touching-in properties, providing near invisible touch-up for areas in critical lighting

### Accreditations

BREEAM Compliant	LEED Compliant	WELL Compliant	EPD Available	Reaction to Fire EN 13501-1
✓	✓	✓	✓	✓

This product has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which is based on ISO 16000 / EN 16516, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 2018 & LEED v4.1 compliant and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. For further information please visit the 'Datasheets and Documents' section of the specific product page at [duluxtrade.co.uk](http://duluxtrade.co.uk)

### KEY BENEFITS

- Anti-flashing
- Dead Matt Finish, Ideal for Ceilings in Critical Lighting
- Excellent Touching-In Properties

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on all normal interior wall and ceiling surfaces.

#### Pack Size

3 L & 10L

#### Colour Range

White only

#### Composition (nominal)

**Pigment:** Lightfast pigments

**Binder:** Copolymer binder

**Solvent:** Water

#### Volume Solids

40% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a first coat of **Dulux Trade Drywall Primer Sealer**. The normal finishing process is 2 or 3 full coats of **Dulux Trade Ultra Matt**, however for significant colour change additional coats maybe required.

### APPLICATION METHOD

Brush, roller, or airless spray.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m<sup>2</sup> per litre.



## ULTRA MATT

### Thinning

Thinning not required.

### Spray Recommendations

**Airless Spray:** For best results use a 515 or 517 Low Pressure tip @ 1300 - 1700 psi (89 – 117 bar).

Alternatively, use a 517 tip @ 2000 – 2400 psi (138 - 165 bar).

*Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.*

### Drying Times

Single coat at standard thickness:

**Touch Dry:** Dependent on temperature and humidity.

**Recoat:** 4 hours.

### Responsible Cleaning

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

#### **Cleaning:**

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.

3. **Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
4. **Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
5. **Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
6. **Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

### ***Do not flush paint down the drain, including when cleaning painting tools***

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: <https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/sustainability](https://duluxtrade.co.uk/sustainability).

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 1g/l VOC. VOC content: Trace (0-0.1%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

**Always read full Health, Safety & Environmental Information on can before use.**

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](https://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2024.