

XTEND+CLIMB Aluminium Professional Telescopic Ladder



Specifications

- Brand: TB Davies - Warranty: 3-year - Max Load: 150kg

- Standard: EN131-6:2019 PROFESSIONAL

- Material: Anodised Aluminium - Commodity Code: 76169990 - Country of Origin: CN - Recommended Usage: Regular

Common Dimensions

- Rung Depth: 35mm

- Distance Between Rungs: 300mm

Packaging Material

- Cardboard Carton/Polystyrene/Polywrap

Availability & Delivery

- Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

[Representative image of product]

Product Description

The all-new Xtend+Climb? ProSeries S2.0 is the Pro-Trade choice when it comes to Telescopic Ladders. Xtend+Climb is still the most comfortable, easy to use and safest telescoping ladder available on the market. Plus it now conforms to the very latest EN131-6 2019 safety standard. Re-designed from the ground up and tested to over 4,000 cycles, the Xtend+Climb features automatic Locking Stabilising Bars, Wall Pads, and Lightning Latch. Using the Xtend+Climb is easier and safer. When you extend the ladder, the Locking Stabilising Bar opens automatically, improving safety, as it's now impossible to use without the stabilising bar in position. Wall Pads create a gap at the top of the ladder so you can comfortably fit your hand over the top rung, and the Lightning Latch is easier to turn and retract the ladder. Rung indicators go green when the ladder is locked and safe to use, yet the ladder is still comfortable to hold and carry from your van to site. All Xtend+Climb ladders are tested to the Professional Grade. The Xtend+Climb is the only Telescopic Ladder you'll ever need.

Features

- Features built-in wall standoff & automatic deploying stabiliser bars
- Aerospace Engineered aircraft grade aluminium alloy for maximum strength
- Double sided feet for durability & traction with padded carrying handle for easy carrying
- Developed with Patented True Telescoping Technology
- Clean-touch Anodised finish keeps your hands oil free

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



XTEND+CLIMB Aluminium Professional Telescopic Ladder

Product Dimensions

SKU	Rungs /Sections	Last Climbing Height (mm)	Approx. Working Height ¹ (mm)	Closed Length (mm)	Extended Length (mm)	Width (mm)	Stabiliser Bar Width (mm)	Depth (mm)	Nett Weight (kg)
1303-080	11 x 1	2300	4050	840	3230	620	863	101	12.6
1303-081	13 x 1	2900	4650	899	3832	618	875	106	15.5

Where applicable, Approx. Working Height¹ is an approximate calculation of 1.75m (5'8") plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of ~75° degrees.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1303-080	880	655	136	0.078	14.1
1303-081	940	655	140	0.086	17.0

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

^{*} Ladder not supplied with Stabiliser Bar.

[†] Heavy Item – 2-person lift required.