

POLYURETHANE VARNISH

Dulux Trade Polyurethane Varnish is a solvent-based interior varnish which gives a tough and durable finish. It can be used over bare wood and previously stained or varnished surfaces. It withstands knocks, scuffs and spills and is suitable for interior wood, veneer, cork and chipboard.

KEY BENEFITS

- Tough & Durable
- Doors, Trim, Furniture and Joinery
- Solvent-Based

PRODUCT INFORMATION

Typical Use

Suitable for interior wood, veneer, cork and chipboard.

Pack Size

1L, 2.5L and 5L.

Colour Range

Clear Gloss, Satin or Matt (2.5L only).

Composition (nominal)

Pigment: Inert matting agents.

Binder: Polyurethane Modified Alkyd.

Solvent: Low Odour aliphatic hydrocarbon.

Volume Solids

49% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be varnished are sound, clean and dry (new surfaces particularly must be fully dry) before treating. Remove all loose and defective coatings, if necessary stripping back to bare wood. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Thoroughly rub down all surfaces in the direction of the grain to provide a 'key', using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

Fill any surface defects, open joints etc. Do not use linseed oil putty for making good with natural wood finishes.

In multi-coat work, it is advisable to lightly rub down between coats, in the direction of the grain, using a suitable grade of abrasive paper and then wipe off with a damp, lint free cloth.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Product is ready to use. Do not thin. Apply up to 3 coats of **Dulux Trade Polyurethane Varnish**. **Dulux Trade Polyurethane Varnish** is not suitable for use on other surfaces such as masonry. On surfaces subject to heavy wear such as flooring, the gloss finish is recommended.

APPLICATION METHOD

Brush only. For Health and Safety reasons relating to all solvent-based paints, spray application is not recommended.

As with all solvent-based paints, do not apply at temperatures below 5°C (as recommended by British Standard BS 6150).

Practical Coverage

On smooth surfaces of average porosity, a guide to the practical coverage is up to 16m² per litre.

Thinning

Do not thin this product.

Spray Recommendations

For Health and Safety reasons relating to all solvent-based paints, this product is not suitable for spray application.

POLYURETHANE VARNISH

Drying Times

Single coat at standard thickness, up to three coats.

Touch Dry: 6-8 hours.

Recoat: 16-24 hours.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Use Paint Thinner:** Use a paint thinner to clean brushes and rollers.
3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash water down the drain or onto the ground.

Do not flush paint down the drain, including when cleaning painting tools

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/e): 400g/l (2010). This product contains max. 399g/l VOC. VOC content: High (25-50%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2023.