# **Solvent Cleaning 98068**



#### **Product Group**

## Cleaning solvents

### **Characteristics**



Product Information

Solvent Cleaning 98068 is a cleaning solvent for metal de-greasing, removal of paint remover residues and final cleaning prior to paint application.

- Compatible with conventional and US products
- Slow evaporating.
- Complies with the German legislation VBF: A2 (flash point >21°C / 70°F).

#### **Specifications**



Qualified Product List Airbus AIMS 09-03-001
Airbus UK ABP 5-1351
Pilatus Britten Norman BNDS 5 Issue 4
British Aerospace Jetstream PS-23-8-30 Issue 2

For most recent up-date or missing specifications please check the qualified product list (QPL) on www.akzonobel.com/aerospace

### **Instruction for Use**



Cleaning of metal surfaces

- Rub the surface thoroughly with clean cloths soaked with Solvent Cleaning 98068 and wipe off with clean dry cloths.
- Do not allow the surface to dry, contamination can be spread.
- The degreased surface should not be touched to avoid contamination prior to paint application



Cleaning of spay equipment

- Remove paint residues with a brush, do not immerse spray guns in Solvent Cleaning 98068 as this may effect non-metallic parts



Cleaning of brushes

- Immerse the brushes in a tray with Cleaning Solvent 98068. After some minutes the paint can be removed from the brush.
- The brushes should not be left in the tray too long, as this may influence the elasticity of the hairs



Note

Solvent Cleaning 98068 does not affect usual metals such as iron, steel, aluminium and magnesium alloys, copper, zinc etc.

Important: Do not use on acrylic windows

Page 1 of 2 (Code 55-04)

## AkzoNobel Aerospace Coatings

# **Solvent Cleaning 98068**



## **Physical Properties**

Flash-point

Solvent Cleaning 98068

>21°C / 70°F



Storage

Store the product dry and at a temperature between 5 and 25°C / 41 and 77°F. Stored in the original unopened containers.

Solvent Cleaning 98068

36 months

## **Safety Precautions**

Comply with all local safety, disposal and transportation regulations. Check the Material Safety Data Sheet (MSDS) and label of the individual products carefully before using the products. The MSDS's are available on request.

### Issue date: August 2009 (supersedes April 2009) - FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given is subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel. Scotch-Brite $^{\otimes}$  is a trademark of 3M.

Page 2 of 2 (Code 55-04)