

Fisheye Eliminator™

Programmed System Technique (PST)
Others
06/14/2021

DESCRIPTION

Lesonal Fisheye Eliminator is a special additive to be used in Lesonal clearcoats to reduce fisheyes in the case of silicone contamination. Lesonal Fisheye Eliminator can be used in any Lesonal clearcoat. Do not use Fisheye Eliminator in Basecoat, Primers, Primer Fillers, or Sealers.

Safety

Considerations




Use suitable personal protection

Akzo Nobel Car Refinishes recommends the use of fresh air supply respirator

Refer to the product Safety Data Sheet (SDS) for more complete safety information.

Mixing



½ to 2 caps of Fisheye Eliminator can be added to 1 liter of any ready to spray Lesonal Clearcoat.

Application



After mixing the clearcoat thoroughly, apply in thinner layers per the clearcoat TDS recommendations.

Allow recommended flash off time between coats. Flash time will be dependent on ambient temperature, applied paint wetness/thickness and available airflow.

Fisheye Eliminator™

Technical Data Sheet
Others
06/14/2021
Page 2 of 3

DESCRIPTION

Lesonal Fisheye Eliminator is a special additive to be used in Lesonal clearcoats to reduce fisheyes in the case of silicone contamination. Lesonal Fisheye Eliminator can be used in any Lesonal clearcoat. Do not use Fisheye Eliminator in Basecoat, Primers, Primer Fillers, or Sealers.

Products and Additives



Lesonal Fisheye Eliminator ○ Item #396725

Basic Raw Materials



Lesonal Fisheye Eliminator ○ Special solvents and anti-silicone agent

Mixing



½ to 2 caps of Fisheye Eliminator can be added to 1 liter of any ready to spray Lesonal Clearcoat.

Application



After mixing the clearcoat thoroughly, apply in thinner layers per the clearcoat TDS recommendations.

Allow recommended flash off time between coats. Flash time will be dependent on ambient temperature, applied paint wetness/thickness and available airflow.

ADDITIONAL INFORMATION

VOC / Regulatory Information



Lesonal Fisheye Eliminator 6.86 lb/gal (823 g/L)

Product Storage



Stock unopened or used products in approved closed containers with proper labeling. Store in moderate temperatures between 40°F - 95°F (5°C – 35°C). Avoid too much temperature fluctuation. Optimum storage temperature is approximately 70°F (20°C).

Lesonal Fisheye Eliminator Item #396725

2 years

Fisheye Eliminator™

Technical Data Sheet
Others
06/14/2021
Page 3 of 3

AkzoNobel Inc., North America

Address: 1845 Maxwell Street – Troy, MI 48084 USA

Telephone: 800.618.1010

FOR PROFESSIONAL USE WITH SUITABLE HSE EQUIPMENT

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.Lesonal.com