

Guncleaner WB

Programmed System Technique (PST)
Thinner
07/17/2015

DESCRIPTION

Cleaning agent specially developed for cleaning and rinsing equipment used for the application of waterborne products.

Safety Considerations



Use suitable respiratory protection

AkzoNobel Car Refinishes recommends providing adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. Use safety eyewear designed to protect against splash of liquids.

In addition to respiratory protection, always wear solvent resistant gloves while cleaning or degreasing, even if working with a low solvent degreaser. This will reduce the risk of cleaning solvents being absorbed into the skin and prevent salts and oils on your hands from contaminating the surface to be refinished.

Read the complete TDS for detailed product information



Guncleaner WB

Technical Data Sheet
Thinner
07.17.2015
Page 3 of 3

DESCRIPTION

Cleaning agent specially developed for cleaning and rinsing equipment used for the application of waterborne products.

PRODUCT AND ADDITIVES

Product

Guncleaner WB - Item #391581

METHOD OF USE

Basic Raw Materials Water and solvents



Before application:

Before spraying water-based products, rinse the gun with Guncleaner WB.

After application:

After emptying the spraygun, immediately rinse thoroughly with Guncleaner WB. Next, dry both the outside and inside of the gun by use of a cloth or pressurized air.

Note: Do not allow aluminum equipment to soak immersed in Autowave Guncleaner. It is advised to select a gun specifically designed and solely to use with water borne products. It is strongly advised to select a spray gun for waterborne products only.

ADDITIONAL INFORMATION

Product Storage



Product shelf-life is determined when products are stored unopened at 20°C. After contact with water/moisture product will have limited shelf life.

Avoid extreme temperature fluctuation.

Product shelf life 4 years at 70°F (20°C)

VOC Information

Ready to Spray VOC

Guncleaner WB Maximum (24 g/liter)

TECHNICAL DATA SHEET NORTH AMERICA



Guncleaner WB

Technical Data Sheet
Thinner
07.17.2015
Page 3 of 3

AkzoNobel Inc., North America

Address: 1845 Maxwell Street - Troy, MI 48084 USA

Telephone: 800.618.1010

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.Lesonal.com